

**PRECISION IRRIGATION SPRINKLERS**

**S60 E - 25° FULL CIRCLE**  
**S60 E - 25° PART CIRCLE**

*LONG THROW*

*Nodolini flange connection*

*Small EUROFLANGE connection*

*Big EUROFLANGE connection (diameter inlet 80 mm)*

*NELSON FLANGE 3"*

*Female thread connection*

*2" BSP*

*2" 1/2 BSP*

*2" NPT*



Nozzle Ø mm	Pressure atm.	Flow l/min	Length of jet m
16	3,0 - 3,5 - 4,0	281 - 304 - 324	33 - 35 - 38
18	3,5 - 4,0 - 4,5	384 - 411 - 436	37 - 40 - 42
20	4,0 - 4,5 - 5,0	506 - 537 - 566	41 - 43 - 45
22	4,0 - 4,5 - 5,0	612 - 649 - 684	43 - 45 - 47
24	4,0 - 4,5 - 5,0	729 - 774 - 816	45 - 47 - 49
26	4,5 - 5,0 - 5,5	908 - 957 - 1004	47 - 49 - 51
28	4,5 - 5,0 - 5,5	1053 - 1110 - 1164	50 - 52 - 54

- Turbine sprinkler
- Conical pipe: high performances
- Perfect functioning on steep terrain
- No vibrations
- No break
- Intermittent jet-breaker adjustable for better uniformity of the rain
- Suitable for irrigation of delicate crops
- The sprinkler can operate with an angle of just 4°

*The technical characteristics are indicative and not binding*