

**PRECISION IRRIGATION SPRINKLERS**
**S60 - 25°**  
**S60 - 25° REVOLVING**  
**S60 - 22°**
**LONG THROW**
*Nodolini flange connection*
*Small EUROFLANGE connection*
*Big EUROFLANGE connection (diameter inlet 80 mm)*
*NELSON FLANGE 3"*
*Female thread connection*
*2" BSP*
*2" 1/2 BSP*
*2" NPT*


Nozzle Ø mm	Pressure atm.	Flow l/min	Length of jet m
20	4,0 - 4,5 - 5,0	506 - 537 - 566	41 - 43 - 45
22	4,0 - 4,5 - 5,0	612 - 649 - 684	43 - 45 - 47
24	4,0 - 4,5 - 5,0	729 - 774 - 816	45 - 47 - 49
26	4,5 - 5,0 - 5,5	980 - 957 - 1004	47 - 49 - 51
28	4,5 - 5,0 - 5,5	1053 - 1110 - 1164	50 - 52 - 54
30	5,0 - 5,5 - 6,0	1273 - 1335 - 1394	53 - 55 - 57

- Turbine sprinkler
- Conical pipe: high performances
- Perfect functioning on steep terrain
- No vibrations
- No break
- Intermittent jet-breaker adjustable for better uniformity of the rain
- Suitable for irrigation of delicate crops
- The sprinkler can operate with an angle of just 4°

*The technical characteristics are indicative and not binding*