Rubinetterie Italiane Velatta SpA
since 1950


GLADIO



# RIV 125

Double-acting hydraulic two-cylinder sliding gate valve, complete with O-ring flanges, PN 10

## >> Technical Drawings and Plates




| Code | DN | P.O. Box | Diameter | H | h | S | L | F | A | D1 | G | Weight | d1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 050125000020 | 8" | 0 | 200 | 510 | 510 | 60 | 432 | M12 | 180 | 295 | M20 | 33,170 | 295 |
| 050125000021 | 10" | 0 | 250 | 634 | 634 | 70 | 498 | - | - | 350 | M20 | 54,400 | 350 |

## >> Advantages

GLADIO is a gate where, in addition to its aesthetic appeal, our engineers have focused above all on functionality and attention to detail, leaving nothing to chance.

To cover a wider range of applications, GLADIO comes standard with dual flanges: one for connection with a standard-size square agricultural flange and one DIN PN 10, or ANSI 150 for the American market.

Thanks to its unique design, GLADIO is a gate valve classified as “clog-resistant,” meaning it can be installed in any position.

Large self-cleaning seat.

Safety: GLADIO is equipped with a sturdy protective

>> RIV Rubinetterie Italiane Velatta S.p.A
Via delle Acacie 8 Zona Industriale D4
P. O.Box 64
28075 GRIGNASCO (NO) ITALY
Tel +39 0163 4151

>> Capitale sociale € 516.000 i.v.
Reg. Imprese di Novara N° 00469610026
R.E.A. di Novara N° 170397
Numero Meccanografico NO009263
Codice Fiscale 00469610026
Partita IVA IT 01399720034

>> E - mail riv-vg@riv-vg.com
vendite.italia@riv-vg.com
export.sales@riv-vg.com

Web www.riv-vg.com

housing that completely isolates the valve's moving parts.

Provision for lever attachments on the valve body.

Stainless steel screws and tie rods to prevent corrosion. Equipped with an open/closed position indicator.

Extremely easy to maintain; all parts are easily replaceable once worn.

Compliant with Directive 97/23/EC (PED).

## >> Technical Data

| | |
|---|---|
| Connection | Square flange / PN 10 |
| Limit | 0°C (+32°F) without liquid +60°C (+140°F) |
| | The maximum operating pressure (PN) applies at an ambient temperature of approximately 23°C. |
| Notes | |
| | Use EN 1092-1 Type 1 (Welding Neck) flanges |