



| TIPO<br>TYPE             | POTENZA ASSORBITA<br>INPUT<br>POWER | AMPERE                   | Q = PORTATA - CAPACITY  |     |     |     |     |     |     |     |      |     |      |
|--------------------------|-------------------------------------|--------------------------|---|-----|-----|-----|-----|-----|-----|-----|------|-----|------|
|                          |                                     |                          | m³/h  | 0   | 1,5 | 3   | 4,5 | 6   | 7,8 | 9   | 10,8 | 12  | 13,8 |
| Monofase<br>Single-phase | P1<br>Watt                          | Monofase<br>Single-phase | lt/1'   | 0   | 25  | 50  | 75  | 100 | 130 | 150 | 180  | 200 | 230  |
| 230V-50Hz                |                                     | 1 x 230V                 | Prevalenza manometrica totale in m.C.A. - Total head in meters w.c. |     |     |     |     |     |     |     |      |     |      |
| JD 200                   | 200 W                               | 0,9                      | H<br>(m)  | 5,5 | 4,4 | 3,2 | 2,2 | 1   |     |     |      |     |      |
| JD 300                   | 300 W                               | 1,3                      |   | 7   | 6,4 | 5,6 | 4,9 | 4   | 2,8 | 1,5 |      |     |      |
| JD 750                   | 750 W                               | 3,5                      |   | 9   | 8,5 | 7,8 | 7   | 5,6 | 5   | 4,2 | 3    | 1,9 | 1    |